

## KONE FROST GLASS PENDANT LUMINAIRE



**TYPE:**

**PROJECT:**

**ORDER NUMBER:**

Model#	Wattage	Voltage
	<b>13, 18, 26</b>	<b>1-120V</b>
	or <b>32</b>	<b>2-277V</b>

**Example:**

6010	26	1
------	----	---


**DELRAY  
LIGHTING  
INCORPORATED**

**6010**

### KONE OPAL PENDANT

Canopy mounts to standard J-box. Electronic ballast fits inside fixture for easy access. Pendant is 6' standard, with steel braided power cord. Finish is silver powder coat. Glass shade is translucent frost. Fixtures have a twist lock socket for secure, easy relamping. Dimming and emergency battery backup are not available. U.L. Listed for damp locations.

**6010**  
Fluorescent



**BURBANK,  
CALIFORNIA,  
91505  
WWW.  
DELRAY  
LIGHTING.  
COM**

JULY 2008

## FLUORESCENT


## BALLAST INFO

### 1-32W PLT



- Standard in universal voltage 120V through 277V.
- .98 power factor with THD<10%.
- End of lamp life protection.

## CP DISTRIBUTION



## COEFFICIENTS OF UTILIZATION

### % CEILING 80 (20% FLOOR)

% WALL	70	50	30
0	96	96	96
1	85	80	76
2	77	69	63
3	70	61	54
4	64	54	46
5	59	48	40
6	54	43	35
7	50	38	31
8	46	34	27
9	43	31	24
10	39	28	21

## NOTES

### 6010.32

1-32W triple tube

G24q-3 electronic twist lock socket

Total lumens: 2400

Spacing criteria: 1.7